



TECHNICAL DATA SHEET

SHIELDING SOLUTIONS CEE-SC001 ELECTRICALLY CONDUCTIVE SILVER PLATED COPPER FILLED SILICONE ELASTOMER

Product overview

CEE-SC001 is an electrically conductive composite material comprising of silicone elastomer and silver-plated copper particles. It is formulated for the production of extruded sections/gaskets that offer a combined high level of EMI shielding and environmental sealing over a wide temperature range. The silicone elastomer base provides excellent resistance to environmental degradation.

CEE-SC001 provides reliable low impedance connections and excellent shielding performance in demanding applications e.g. waveguide gaskets, EMP protection, base station applications etc.

Cured Properties

Colour	Tan
Density	3.5gcm ⁻³
Hardness	65 Shore A
Volume resistivity	<0.005Ω.cm
Tensile strength	2.0MPa
Elongation (minimum before break)	100%
Compression set – 72 hours at 100°C	<25%
Service temperature range	-55°C to 160°C



TECHNICAL DATA SHEET

SHIELDING SOLUTIONS CEE-SC001 ELECTRICALLY CONDUCTIVE SILVER PLATED COPPER FILLED SILICONE ELASTOMER

Shielding Effectiveness

200kHz (H field)	80dB
100MHz (E field)	110dB
500MHz (E field)	110dB
2GHz (Plane wave)	115dB
10GHz (Plane wave)	115dB

Available forms

This material is available in a wide range of solid and hollow profiles such as 'O' sections, 'D' sections, 'U' channels, etc. The equivalent material type (CEM-SC001) is also available as moulded components, sheets and flat gaskets. In either form gaskets or sheet material can be supplied with a self adhesive backing to assist installation / assembly.



Shielding Solutions Ltd
Unit 17
46 Springwood Drive
Braintree
Essex
CM7 2YN

Tel: 01376 330033

Fax: 01376 339163

Web: www.shielding-solutions.com

SSL/TDS/130 ISS 1

20/07/2008